

# Profinish

Weather Resistant, Smooth, Fine and Texture Finish Coat and Plaster

|                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Description                | It is a high quality cement based, fine smooth or texture finish coat and plaster. It is used for walls, ceiling of concrete, masonry or plastered surfaces .It's suitable for interior and exterior exposure subjected to humidity, water and coastal                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Where to use               | <ul style="list-style-type: none"> <li>• Interior and Exterior surfaces (wet or dry)</li> <li>• Concrete and masonry.</li> <li>• plastered and rendered surfaces.</li> <li>• Fill cracks, levels the plaster surface.</li> <li>• Gives better adhesion to paints</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Advantages                 | <ul style="list-style-type: none"> <li>• Weather and water resistant.</li> <li>• Thin, smooth and fine.</li> <li>• Economic and easy to use.</li> <li>• Free of chlorides.</li> <li>• UV resistant.</li> <li>• Available in Color's.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Properties                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Color                      | Grey, white & Standard colors                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Specific gravity - Dry     | 1.5                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Setting time               | 2 hours @ 25 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Complying with B.S.EN998-1 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Surface Preparation        | <ul style="list-style-type: none"> <li>• Remove dust, loose particles and foreign matters.</li> <li>• Maintain sufficient wetting</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Mixing                     | <ul style="list-style-type: none"> <li>• Add the material to clean water 7 L – 8 L or mixing liquid of <b>Kemlatex SBR</b> or <b>Kembond SBR</b> and water at 1:1</li> <li>• Mix for 2-3 minutes and let the mix to stand for 15 minutes and mix again mechanically for further 1 minute</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Application                | <ul style="list-style-type: none"> <li>• Apply the material by spraying, troweling or rollers.</li> <li>• Cure with water for 2 days for exterior hot and dry conditions.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Cleaning                   | All tools, equipment should be washed with water after use.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Theoretical Coverage       | <ul style="list-style-type: none"> <li>• For fine plaster 0.75 Kg/m<sup>2</sup>/ 0.5 mm Thickness</li> <li>• For texture coat 1.5 Kg/m<sup>2</sup>/1mm Thickness</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Packaging                  | 20 Kg sacks                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Shelf life & Storage       | 12 months in its unopened packs stored in appropriate conditions                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Health and Safety          | <ul style="list-style-type: none"> <li>• Use goggles, Gloves and breathing mask when applying.</li> <li>• <b>Profinish</b> is non-toxic. Any splashes to the skin should be washed immediately with water.</li> <li>• Splashes to the eyes should be washed</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Additional Information     | <p><b>PROKEM</b> provides the construction industry with a comprehensive range of construction chemicals and specialty products answering the queries of modern engineers for trouble free durable structure.</p> <p><b>PROKEM</b> designs tailor made products should there be critical application that requires specific properties rather than our main range. For our customer's satisfaction, <b>PROKEM</b> reserves the right to change the properties of its products.</p> <p>All orders are accepted subject to our current term of sale &amp; delivery.</p> <p>Users must always refer to the most recent issue of the local product data sheet for the product concerned, copies of which will be supplied on request.</p> <p><b>PROKEM</b> extends technical services to include after sales support to assist users in</p> |