

Berefex

Outdoor & Indoor Smoothing and Leveling Putty



Description	Berefex is a ready-to-use outdoor and indoor putty made of acrylic copolymer resin, fillers & special additives. Berefex is a high quality, easy to use & time saving putty.
Where to use	• Berefex is used for smoothing and leveling outdoor and indoor walls as well as ceilings prior to the use of emulsion coating. • Berefex when applied in several passes may also be used to fill holes and cracks (without any movement) in cement and gypsum plasters.
Advantages	• Good whiteness & non-toxic. • Can be sanded & can penetrate the pores. • Minimal shrinkage. • Excellent workability and ease of use Good adherence to smooth substrates e.g. fair face concrete. • Leaves no odor after application.
Properties	
Finish Aspect	Matt
Density	1.75 Kg/lit.
% Volume Solids	55% ±1%
Color	White
How to use	Substrate must be clean, sound and free from dust, grease and oil. All loose particles must be removed by mechanical means Absorbent substrates should preferably be moistened with water and sealed with Prosealer A Berefex is applied using a knife or a plaster trowel. Surfaces must be completely dry between successive coats (minimum 2 hours drying time, according to humidity and temperature) It is advisable to apply 2 layers within 24 hours or less between each layer (according to temperature). Substrates should be sanded and then apply the appropriate paint. For exterior application, the substrate should be primed with Prosealer A, then apply a thin layer of Berefex.
Cleaning	Clean tools directly after use with water.
Theoretical Coverage	0.35 - 1 kg/m ² according to surface conditions.
Packaging	5 Kg plastic sacks 20 Kg plastic sacks
Shelf life & Storage	Berefex can be stored for up to 12 months in an original sealed pack within recommended storing conditions (kept away from direct sunlight and high temperature areas)
Health and Safety	Use gloves to avoid contact with skins. If skin comes in contact, wash immediately with soap and water. Do not use solvents. Eye contamination must be immediately washed with water, then seek medical treatment. Working areas should be well ventilated.
Additional Information	PROKEM provides the construction industry with a comprehensive range of construction chemicals and specialty products answering the queries of modern engineers for trouble free durable structure. PROKEM designs tailor made products should there be critical application that requires specific properties rather than our main range. For our customer's satisfaction, PROKEM reserves the right to change the properties of its products. All orders are accepted subject to our current term of sale & delivery. Users must always refer to the most recent issue of the local product data sheet for the product concerned, copies of which will be supplied on request. PROKEM extends technical services to include after sales support to assist users in a proper handling of our products.