

# Inplast 102

High Quality Washable Emulsion Interior Paint

|                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Description            | <b>Inplast 102</b> is an acrylic Matt emulsion decorative indoor paint, with a very good flat smooth durable surface.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Where to use           | <ul style="list-style-type: none"> <li>• <b>Inplast 102</b> is used for interior applications on old plaster as well as new plaster, concrete, wood and old emulsion paint.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Advantages             | <ul style="list-style-type: none"> <li>• Durable excellent protection.</li> <li>• Excellent Color stability &amp; waterproof.</li> <li>• Gives a very good flat smooth durable surface.</li> <li>• Economic, easy to apply &amp; non yellowing.</li> <li>• Easy to maintain.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Properties             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Finish Aspect          | Matt                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Specific Gravity       | 1.45 - 1.50                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Drying time            | 3-4 hours @ 23 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Dry to recoat          | 5-6 hours @ 23 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| % Volume Solids        | 60-65%                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Color's                | White and a high range of Color's available.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Surface Preparation    | <ul style="list-style-type: none"> <li>• Surfaces must be free from dust, grease and oil stains.</li> <li>• Surface must be primed with <b>Prosealer A</b>.</li> <li>• Fill cavities and cracks with <b>Berefex</b> then use <b>Berefex</b> to level the surface.</li> <li>• Surfaces has to be sanded before painting.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Application            | <ul style="list-style-type: none"> <li>• Mix the product in its container thoroughly manually or mechanically to get a uniform color.</li> <li>• Emulsion must be mixed before use and surfaces should be sanded.</li> <li>• Apply using brush, roller. Spray gun can also be used.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Theoretical Coverage   | 0.2 Kg/m <sup>2</sup> at 85 microns D.F.T<br>Minimum of 2 coats are required                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Packaging              | 5 & 20 Kg plastic pails                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Shelf life & Storage   | Storage can reach 12 months in a day place, away from direct sunlight and high temperatures.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Health and Safety      | <ul style="list-style-type: none"> <li>• Use gloves to avoid contact with skins.</li> <li>• If skin comes in contact, wash immediately with soap and water.</li> <li>• Do not use solvents.</li> <li>• Eye contamination must be immediately washed with water, then seek medical treatment.</li> <li>• Working areas should be well ventilated.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Additional Information | <p><b>PROKEM</b> provides the construction industry with a comprehensive range of construction chemicals and specialty products answering the queries of modern engineers for trouble free durable structure.</p> <p><b>PROKEM</b> designs tailor made products should there be critical application that requires specific properties rather than our main range. For our customer's satisfaction <b>PROKEM</b> reserves the right to change the properties of its products.</p> <p>All orders are accepted subject to our current term of sale &amp; delivery.</p> <p>Users must always refer to the most recent issue of the local product data sheet for the product concerned, copies of which will be supplied on request.</p> <p><b>PROKEM</b> extends technical services to include after sales support to assist users in</p> |