

Propatch Binder

Non-Shrink Acrylic Sand, Cement Leveling and Repairing Binder

Description	100% acrylic emulsion liquid binder, sand and cement powder designed for on-site leveling and repairing cracks and low spots and depression up to 20 mm deep and 25 mm width on sport surfaces.
Where to use	Tennis courts. Multi-purpose courts. Concrete and asphalt.
Advantages	Better release properties. Non-staining. Does not affect cement hydration.
Properties	
Base	Acrylic emulsion
Color	Milky white
Density	1.2 ±0.2 Kg/m ³
Surface Preparation	Surfaces must be clean from dust, dirt, debris and loose material. New concrete or asphalt must cure 28 days.
Application	Apply with a smooth trowel or squeegee for leveling. Apply in multiple lifts to achieve desired depth in patches greater than 25 mm. Allow surfaces to cure for 24 hours.
Theoretical coverage	1.2 Kg /m ² for 1 mm thickness. Maximum thickness is 12 mm.
Packaging	20 Kg sacks and pails 5 Kg sacks and pails
Shelf life & Storage	One year in its original packs stored at recommended conditions.
Health and Safety	Use gloves to avoid contact with skins. If skin comes in contact, wash immediately with soap and water. Do not use solvents. Eye contamination must be immediately washed with water, then seek medical treatment. Working areas should be well ventilated.
Additional Information	PROKEM provides the construction industry with a comprehensive range of construction chemicals and specialty products answering the queries of modern engineers for trouble free durable structure. PROKEM designs tailor made products should there be critical application that requires specific properties rather than our main range. For our customer's satisfaction. PROKEM reserves the right to change the properties of its products. All orders are accepted subject to our current term of sale & delivery. Users must always refer to the most recent issue of the local product data sheet for the product concerned, copies of which will be supplied on request. PROKEM extends technical services to include after sales support to assist users in a proper handling of our product.