

Decacoat W Putty

Outdoor & Indoor Putty for Crack Filling

Description	Decacoat W Putty is a ready-to-use outdoor and indoor acrylic co-polymer joint and crack filling putty and also can be used for smoothing and leveling of plaster surface. It is a high quality, easy to use and time saving putty.
Where to use	• Decacoat W putty is used for: • Filling cracks, pores, blowholes. • Filling around windows and door frames to building elements as plaster and stones. • Indoor and outdoor applications. • Smoothing and leveling of blaster surface
Advantages	• Ready to use. • Excellent workability. • Good adherence. • Odorless & non-toxic.
Properties	
Sp. gr.	1.74 ±0.05
Color	White & others
Curing Time @ 23 °C	
Touch dry	45 – 60 min.
Recoating	3 – 4 hours
Full Cure	7 days
UV-Resistance	Excellent
Outdoor Durability	Excellent.
Surface Preparation	• Surfaces must be clean, sound, and free from dirt, grease and loose particles. • Absorbent surfaces should be moistened with water and sealed with Prosealer A
Mixing	• Stir the contents of the pack until a homogeneous consistency.
Application	• The material is applied using a spatula, knife or steel trowels. • Surfaces must be completely dry between successive applications.
Cleaning	• Clean tools directly after use with water.
Theoretical Coverage	0.5 – 1.0 Kg/m ² (depending on surface conditions).
Packaging	5 & 20 kg. plastic bags.
Shelf life & Storage	Decacoat W Putty can be stored for up to 12 months in an original sealed pack within recommended storing conditions (kept away from direct sunlight and high temperature)
Health and Safety	• This product is of low toxicity but normal precautions should be observed. • Wear gloves, and if working overhead or spraying, wear goggles. • Wash off any skin splashes with soap and water. Eye contamination should be treated by irrigating the eye with an eye bathing solution. • Ensure adequate ventilation in confined spaces and use breathing aids. If ingested, drink milk or water and seek medical attention.
Additional Information	PROKEM provides the construction industry with a comprehensive range of construction chemicals and specialty products answering the queries of modern engineers for trouble free durable structure. PROKEM designs tailor made products should there be critical application that requires specific properties rather than our main range. For our customer's satisfaction, PROKEM reserves the right to change the properties of its products. All orders are accepted subject to our current term of sale & delivery. Users must always refer to the most recent issue of the local product data sheet for the product concerned, copies of which will be supplied on request. PROKEM extends technical services to include after sales support to assist users in a proper handling of our products.