

Kemtrack



Cushioned Acrylic Layer for Running Floors

Description	It is a part of Prodeco sports flooring system combined of an acrylic emulsion mixed with graded granular rubber particles designed to impart excellent flexibility to running tracks and sport flooring.
Where to use	Running flooring tracks. Field event surfaces. Sport floors.
Advantages	Flexible and durable. Protection against oxidation and moisture. Reduce maintenance cost. Prolong the life expectancy.
Properties	
Type	Acrylic emulsion
Specific Gravity	1.2 ±0.31
Flammability	Non flammable
Flash Point	None
Recoating time @ 25 °C	1 — 2 hours
Drying time @ 25 °C	24 hours
Color	Blue, Red and Green – other colors can be available upon request
Surface Preparation	- The surface must be clean of dust, dirt, debris and loose materials. - New concrete or asphalt surfaces must cure for 28 days.
Mixing	- Stir before using. - Temperature must be +10 °C to 30 °C during application.
Application	Depressions and shallow or damaged areas must be patched with Propatch binder. Surfaces must be primed with Bonding primer @ 0.1 – 0.15 Kg/m². Apply Prodeco S at 0.5 Kg/m² Apply Prodeco Cushion: Coarse layer: 1.5 Kg/m² for a layer of 1 mm thickness, recommended a minimum of 3 mm Fine layer: 1.0 Kg/m²/layer 1 mm thickness, recommended 2 mm Apply Kemtrack at 2.5 Kg/m² for a thickness of 2 mm Apply a top coat of Prodeco P at 0.25 Kg/m²/ Coat – Minimum of 2 coats are recommended Allow to dry before use for 24 hours. Do not apply if rain is imminent or forecast.
Cleaning	Clean all tools after use with water.
Theoretical Coverage	2.5 Kg/m ² / Layer for a 2 mm thickness.
Packaging	20 Kg Pails
Shelf life & Storage	It has a shelf life of 12 months if kept in their original packaging in a dry condition.
Health and Safety	Use goggles, gloves and a breathing mask when applying. Apply forced ventilation in confined spaces. Remove splashes from skin with hand cleaner or soap and water. Eye splashes to be washed with plenty of water. If ingested seek medical advice.
Additional Information	PROKEM provides the construction industry with a comprehensive range of construction chemicals and specialty products answering the queries of modern engineers for trouble free durable structure. PROKEM designs tailor made products should there be critical application that requires specific properties rather than our main range. For our customer's satisfaction. PROKEM reserves the right to change the properties of its products. All orders are accepted subject to our current term of sale & delivery. Users must always refer to the most recent issue of the local product data sheet for the product concerned, copies of which will be supplied on request. PROKEM extends technical services to include after sales support to assist users in a proper handling of our product.