

Kemfloor Traffic / EP

Epoxy-Based Traffic Paint

Description	It is a fast drying epoxy-based traffic paint with excellent wearing and abrasion resistant
Where to use	It designed to be used as a traffic paint and as an interior coating for: •Concrete sidewalks •Decks •Indoor roads and courts •Asphalt and wood
Advantages	Easy to be applied by brush or roller on asphalt and cementitious surfaces Very good flow giving a smooth appearance resistant to water and sea water High wearing and abrasion resistance Good resistance to mild chemicals Very good color retention A special grade for UV resistance – upon request
Properties	
Color	Grey - other colors are available on request
Mass Density Approximately	1.5 Kg/m ³
Solids Content	100% by volume
Touch Dry	60 - 80 minutes @25 °C
Hard Dry	24 hours @25 °C
Surface Preparation	Surfaces must be clean from dust, dirt, debris and loose material
Mixing	Stir the material (A & B) in its container and mix thoroughly before use
Application	Apply the material with brush or roller over a proper surface preparation Apply 2 – 3 coats with time between coats up to 60 minutes Leave to dry for a 24 hours
Cleaning	Clean all tools immediately after work with Prosolve EP
Theoretical coverage	0.15 Kg/m ² for 100 micron
Packaging	5 Kg cans (A&B) 25 Kg cans (A&B)
Shelf life & Storage	One year in its original cans stored at the suitable conditions
Health and Safety	Use goggles, Gloves and breathing mask when applying Applied forced ventilation in confined spaces Skin splashes to be removed with hand cleaner, soap and water Eye splashes to be washed with plenty of water If ingested seek medical advice
Additional Information	PROKEM provides the construction industry with a comprehensive range of construction chemicals and specialty products answering the queries of modern engineers for trouble free durable structure PROKEM designs tailor made products should there be critical application that requires specific properties rather than our main range. For our customer's satisfaction PROKEM reserves the right to change the properties of its products All orders are accepted subject to our current term of sale & delivery Users must always refer to the most recent issue of the local product data sheet for the product concerned, copies of which will be supplied on request PROKEM extends technical services to include after sales support to assist users in a proper handling of our product