

Berefex flex

Outdoor & Indoor Putty for Crack Filling

Description	Berefex flex is a ready-to-use outdoor and indoor acrylic joint and crack filling putty. Berefex flex is a high quality, easy to use and time saving putty.
Where to use	• Berefex flex is used for filling cracks, pores, blowholes and windows and door frames to building elements as plaster and stones. • It is used for both indoor and outdoor applications.
Advantages	• Ready to use • Flexible • Excellent workability • Good adherence • Odorless
Properties	
Specific Gravity	1.3 ±0.2
Color	White & others
Curing Times @ 25 °C	7 days
Full Cure	
Touch dry	45 – 60 minutes
Recoating	3 – 4 hours
Full Cure	7 days
UV-Resistance	Excellent
Outdoor Durability	Excellent
Surface Preparation	• Surfaces must be clean, sound, and free from dirt, grease and loose particles. • Absorbent surfaces should be moistened with water and sealed with Prosealer A
Mixing	Stir the contents of the pack until a homogeneous consistency.
Application	• The material is applied using a spatula, knife or steel trowels. • Surface must be completely dry between successive applications.
Cleaning	Clean tools directly after use with water.
Theoretical Coverage	0.5- 1.0 Kg/ m ² According to crack conditions
Packaging	5 Kg plastic bags 20 Kg plastic bags
Shelf life & Storage	Berefex flex can be stored for up to 12 months in an original sealed pack within recommended storing conditions (kept away from direct sunlight and high temperature areas)
Health and Safety	• Use gloves to avoid contact with skins. • If skin comes in contact, wash immediately with soap and water. • Do not use solvents. • Eye contamination must be immediately washed with water, then seek medical treatment. • Working areas should be well ventilated.
Additional Information	PROKEM provides the construction industry with a comprehensive range of construction chemicals and specialty products answering the queries of modern engineers for trouble free durable structure. PROKEM designs tailor made products should there be critical application that requires specific properties rather than our main range. For our customer's satisfaction, PROKEM reserves the right to change the properties of its products. All orders are accepted subject to our current term of sale & delivery. Users must always refer to the most recent issue of the local product data sheet for the product concerned, copies of which will be supplied on request. PROKEM extends technical services to include after sales support to assist users in a proper handling of our products.